

CERTIFICATE OF COMPLIANCE

Certificate Number R40239
Report Reference R40239-20200817
Issue Date 2020-AUGUST-17

Issued to: HAFELE GMBH & CO KG
Adolf-Hafele-Str. 1
Nagold, 72202 DE

**This certificate confirms that
representative samples of**

GASKETING AND EDGE-SEALING MATERIALS FOR
FIRE DOORS, POSITIVE-PRESSURE TESTED

See addendum page for models

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety:
Additional Information:

UL 10C - Positive Pressure Fire Tests of Door Assemblies

See the UL Online Certifications Directory at
<https://iq.ulprospector.com> for additional information.

This *Certificate of Compliance* does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number R40239
Report Reference R40239-20200817
Issue Date 2020-AUGUST-17

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Single-sided threshold seals for use with Listed steel frames and/or Classified steel-covered composite, hollow-metal doors, wood and plastic-covered composite doors rated up to-1/2 h; and wood core doors rated 20 min:
DDS 12, DDS 12 S.

Double-sided threshold seals for use with Listed steel frames and/or Classified steel-covered composite, hollow-metal doors, wood and plastic-covered composite doors rated up to-1/2 h; and wood core doors rated 20 min:
DDS 12, DDS 12 S.

Single-sided threshold seals, for use with listed steel frames and/or classified steel-covered composite, hollow-metal doors rated up to 3 h; wood and plastic-covered composite doors rated up to 1-1/2 h and wood core doors rated 20 min: DDS 15

Double-sided threshold seals, for use with listed steel frames and/or classified steel-covered composite, hollow-metal doors rated up to 3 h; wood and plastic-covered composite doors rated up to 1-1/2 h and wood core doors rated 20 min: DDS 20

Single-sided threshold seals, for use with listed steel frames and/or classified steel-covered composite, hollow-metal doors rated up to 3 h; wood and plastic-covered composite doors rated up to 1-1/2 h and wood core doors rated 20 min: DDS 20



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

